

Eagle Eye Camera DZ03

Indoor/Outdoor 5MP Mini PTZ IP Camera, 4.7-56.4mm Motorized Zoom Lens, POE+, IR




The Eagle Eye DZ03 is a high performance 5 Megapixel PTZ that incorporates all the features necessary to get clarity under both day and night conditions. The durable aluminum housing is easy to mount. The camera comes pre-configured to securely operate with the Eagle Eye Cloud VMS. No configuration is needed. Just connect and start recording video. Best for small outdoor areas or any size indoor area.

Key Features

> 5 Megapixel

- > Indoor/Outdoor Weatherproof Dome
- > Durable All-Aluminum Housing
- > Motorized Lens, 4.7–56.4mm Zoom and Focus
- > Wide Dynamic Range
- > Night Vision Smart IR, Up to 80m Range
- > Triple RTSP Streams

Dimension Drawing



| Camera | |
|-----------------------------|---|
| Pixels | 5 MP |
| Resolutions | 2560×1920/2048×1536/1280×960 @25/30fps, D1/VGA/640×360/CIF/QVGA @25/30fps, VGA/CIF/QVGA @25/30fps |
| Lens | 4.7 – 56.4mm motorized lens, 12X optical zoom, 16X digital zoom |
| Night Vision | Up to 80m (262ft) |
| Field of View | 60.9° – 6.43° |
| Dynamic Range | Wide dynamic range (120dB) |
| Digital Noise Reduction | Yes, with defog capability |
| Digital Image Stabilization | Automatic |
| Applications | Best for indoor/outdoor deployments that require a medium level of zoom capabilities |
| Image Sensor | 1/2.8" progressive scan CMOS |
| Iris | Fixed |
| Shutter Speed | 1/5s to 1/20000s |
| Min Illumination | Color 0.01 Lux; IR on 0 Lux |

| Digital Capabilities | |
|-----------------------------|---|
| Video Compression | H.264/265 high/main/baseline, MJPEG |
| Audio Compression | G.711, RAW_PCM |
| Image Settings | Rotation, saturation, brightness, contrast, sharpness |
| Corridor Mode | N/A |

| Preconfigured with secure password, plug and play |
|---|
| Fully integrated with Eagle Eye Cloud VMS |
| Eagle Eye Verified |
| |

| Interface | |
|------------------------|--------------------------------------|
| Ethernet | Waterproof RJ-45 female 10/100Base-T |
| External I/O Terminals | Alarm in, alarm out |
| Audio | 1Ch audio in, 1Ch audio out |
| BNC Output | N/A |
| Edge Storage | microSD/SDHC/SDXC slot, max 64GB |

| Physical/Power | |
|-----------------------|------------------------------------|
| Power | AC 24V/POE+, power supply included |
| Power Consumption | Less than 25W |
| Operating Temperature | -40°C to +60°C (-40°F to 140°F |
| Operating Humidity | 0% – 90% RH |
| Waterproof | IP66 |
| Approvals | CE/FCC |
| Dimensions | Φ130 × 112mm (5.12 x 4.41in) |
| Weight | 1.5kg (3.3lb) |
| Housing | Aluminum and composite |

| Lagie Lye Part Numbers | | |
|------------------------|---|--|
| EN-CDUZ-003a | Eagle Eye Camera DZ03 Indoor/Outdoor Dome 5MP, IR, IP66, 4.7mm-56.4mm Moto lens, POE+ | |
| EN-CAWA-003 | Eagle Eye Camera Wall Arm WA003 (DZ03) | |
| EN-CAPE-002 | Eagle Eye Camera Pendant PE002 (DZ03) | |
| EN-CABX-004 | Eagle Eye Camera Junction Box BX004 (WA03,PE02,DF03) | |
| EN-RRCO2 | Eagle Eye Camera+ Rapid Replacement | |
| | | |

Version 1.1 20210817 Copyright 2021 Eagle Eye Networks, Inc. WWW.een.com