

Eagle Eye Camera DZ06

Indoor/Outdoor 5MP 30x Starlight PTZ IP Camera, 5.3–159mm Motorized Zoom Lens, POE+, IR, ONVIF Profile S, NDAA Compliant



CAMERA

| Pixels | 5 MP |
|--|---|
| Resolutions | 2880×1620, 2560×1440, 2304×1296, 1920×1080, 1280×720 @25/30fps |
| Lens | 5.3–159 mm |
| IR Illumination Range | IR distance up to 200 m (656.2 ft) |
| Pan/Tilt/Rotation Range | Pan: 0° ~ 355° endless/Tilt: -20° ~ +90° (auto-flip) |
| Dynamic Range | True WDR |
| Digital Noise Reduction | 2D/3D DNR |
| | |
| Digital Image Stabilization | Automatic |
| Digital Image Stabilization Applications | Automatic Best for wide outdoor areas like campuses, critical infrastructure, and city intersections |
| <u> </u> | Best for wide outdoor areas like campuses, critical |
| Applications | Best for wide outdoor areas like campuses, critical infrastructure, and city intersections |
| Applications Image Sensor | Best for wide outdoor areas like campuses, critical infrastructure, and city intersections 1/2.8" progressive scan CMOS |

DIGITAL CAPABILITIES

| Video Compression | H.265, H.264, and MJPEG |
|----------------------------------|---|
| Image Settings | Saturation, brightness, contrast, sharpness |
| Corridor Mode | No |
| | |
| SETUP | |
| SETUP Eagle Eye Cloud VMS | Preconfigured with secure password, plug and play |

INTERFACE

Cyber Secure

| Ethernet | 1 Ethernet (10/100 Base-T) RJ-45 Connector |
|--------------|--|
| Audio | 1ch Input, 1ch Output |
| Physical I/O | 2ch Input, 2ch Output |

Eagle Eye Verified


PHYSICAL/POWER

| Power 24VAC/36VDC/PoE+ (802.3at), Standard Equipped: 36VDC Power Consumption Less than 24 W Operating Temperature -40°C to 60°C (-40°F to 140 °F) Operating Humidity Less than 90% RH Ingress Protection IP66 Approvals CE-EMC/FCC Dimensions Ø176.0 × 303.9 mm (Ø6.93 × 11.96 in.) Weight and Housing 4 kg (8.82 lb), Metal | | |
|---|-----------------------|---------------------------------------|
| Operating Temperature -40°C to 60°C (-40°F to 140 °F) Operating Humidity Less than 90% RH Ingress Protection IP66 Approvals CE-EMC/FCC Dimensions Ø176.0 × 303.9 mm (Ø6.93 × 11.96 in.) | Power | 7 7 7 7 111 |
| Operating Humidity Ingress Protection IP66 Approvals CE-EMC/FCC Dimensions Ø176.0 × 303.9 mm (Ø6.93 × 11.96 in.) | Power Consumption | Less than 24 W |
| Ingress Protection | Operating Temperature | -40°C to 60°C (-40°F to 140 °F) |
| Approvals CE-EMC/FCC Dimensions Ø176.0 × 303.9 mm (Ø6.93 × 11.96 in.) | Operating Humidity | Less than 90% RH |
| Dimensions Ø176.0 × 303.9 mm (Ø6.93 × 11.96 in.) | Ingress Protection | IP66 |
| , | Approvals | CE-EMC/FCC |
| Weight and Housing 4 kg (8.82 lb), Metal | Dimensions | Ø176.0 × 303.9 mm (Ø6.93 × 11.96 in.) |
| | Weight and Housing | 4 kg (8.82 lb), Metal |

The Eagle Eye DZ06 5MP 30x Starlight PTZ camera is ideal for securing wide outdoor areas like campuses, critical infrastructure, and city intersections. With 30x zoom, long-range IR, and Al-powered tracking, it excels in perimeter defense, traffic monitoring, and public safety — especially in low-light or high-risk environments.

Key features

- 30x optical zoom with 5MP resolution
- · Al-Powered auto tracking and detection
- Superior low-light performance with AI-ISP



EAGLE EYE PART NUMBERS

| EN-CDUZ-006a | Eagle Eye Camera DZ06 30x Starlight PTZ 5Mpix, 5.3–159 mm Motorized Zoom Lens, POE+, IR, Wall Arm Included |
|--------------|--|
| EN-RRC04-1 | Eagle Eye Camera L4 Ext Warranty and Rapid Replacement Monthly |
| EN-CABX-013 | Eagle Eye Camera Large Format Junction Box BX013 |
| EN-CAPE-005 | Eagle Eye Camera Pendant PE005 |
| EN-CAPM-003 | Eagle Eye Camera Pole Mount PM003 |
| EN-CACM-003 | Eagle Eye Camera Corner Mount CM003 |