

Eagle Eye DD09 Vandal Dome Camera

Indoor/Outdoor 4MP IP Camera, 2.7-13.5 mm Lens, POE, IR



CAMERA

CAMERA	
Pixels	4 MP
Resolutions	2592×1520/2560×1440/2304×1296/ 1920×1080/1280×720 @25/30 fps
Lens	2.7–13.5 mm motorized lens
Night Vision	Smart IR LEDs, 30 m (98.4 ft) range
Field of View	34.3-103°
Dynamic Range	WDR (120 dB) and HLC/BLC
Digital Noise Reduction	2D/3D DNR and defog
Digital Image Stabilization	Automatic
Applications	Best for modest outdoor areas or large indoor areas: small parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses
Image Sensor	1/3" progressive scan CMOS
Iris	Fixed-Iris
Shutter Speed	1/5–1/20000 s
Min Illumination	Color 0.05 Lux; IR on 0 Lux

DIGITAL CAPABILITIES

Video Compression	H.265, H.264, and MJPEG
Image Settings	Rotation, saturation, brightness, contrast, sharpness
Corridor Mode	Yes
SETUP	
Eagle Eye Cloud VMS	Preconfigured with secure password, plug and play
Camera Settings	Fully integrated with Fagle Eye Cloud VMS and Fagle

Eye CameraManager
Eagle Eye Verified

Cyber Secure INTERFACE

Ethernet	Waterproof RJ-45 female 10/100 Base-T
External I/O Termainals	Alarm in, alarm out
Audio	1 ch input, 1 ch output
BNC Output	Built-in CVBS output
Edge Storage	microSD/SDHC/SDXC slot, max 128GB


PHYSICAL/POWER

PowerDC12V; POE+ (IEEE 802.3af)Power Consumption3.5W (IR off); 8W (IR on)Operating Temperature-30 °C to 50 °C (-22 °F to 122 °F)Operating HumidityLess than 90% RHIngress ProtectionIK10, IP66ApprovalsCE/FCCDimensionsΦ140 × 110 mm (Φ5.51 × 4.33 in.)Weight0.630 kg (1.39 lb)HousingAll aluminum	FITTSICAL/FOWER	
Operating Temperature -30 °C to 50 °C (-22 °F to 122 °F) Operating Humidity Less than 90% RH Ingress Protection IK10, IP66 Approvals CE/FCC Dimensions Φ140 × 110 mm (Φ5.51 × 4.33 in.) Weight 0.630 kg (1.39 lb)	Power	DC12V; POE+ (IEEE 802.3af)
Operating Humidity Less than 90% RH Ingress Protection IK10, IP66 Approvals CE/FCC Dimensions Φ140 × 110 mm (Φ5.51 × 4.33 in.) Weight 0.630 kg (1.39 lb)	Power Consumption	3.5W (IR off); 8W (IR on)
Ingress Protection IK10, IP66 Approvals CE/FCC Dimensions Φ140 × 110 mm (Φ5.51 × 4.33 in.) Weight 0.630 kg (1.39 lb)	Operating Temperature	-30 °C to 50 °C (-22 °F to 122 °F)
Approvals CE/FCC Dimensions Φ140 × 110 mm (Φ5.51 × 4.33 in.) Weight 0.630 kg (1.39 lb)	Operating Humidity	Less than 90% RH
Dimensions Φ140 × 110 mm (Φ5.51 × 4.33 in.) Weight 0.630 kg (1.39 lb)	Ingress Protection	IK10, IP66
Weight 0.630 kg (1.39 lb)	Approvals	CE/FCC
	Dimensions	Φ140 × 110 mm (Φ5.51 × 4.33 in.)
Housing All aluminum	Weight	0.630 kg (1.39 lb)
	Housing	All aluminum

The Eagle Eye DD09 is a high-performance 4 Megapixel camera with IP66 environmental and IK10 vandal rating. This dome features a junction-style interface for easier installation and is suitable for both indoor and outdoor applications. The camera comes pre-configured to securely operate with the Eagle Eye Cloud VMS and Eagle Eye CameraManager.

Key features

- 4 Megapixel
- Indoor/outdoor waterproof vandal dome
- Junction-style termination
- Durable all-aluminum housing, IP66 & IK10
- Motorized lens, 2.7-13.5 mm
- · Wide dynamic range
- Night vision Smart IR, IR LEDs, 30m range
- Triple RTSP streams





EAGLE EYE PART NUMBERS

EN-CDUD-009a	Eagle Eye Camera DD09 Indoor/Outdoor Dome 4MP, No Pigtail, H265, IR, IP66, IK10, 2.7mm–13.5m Moto
EN-RRC01	Eagle Eye Camera Rapid Replacement
EN-CAPE-004	Eagle Eye Camera Pendant
EN-CAWA-006	Eagle Eye Camera Wall Arm
EN-CAWA-007	Eagle Eye Camera Wall Arm with Junction Box
EN-CAPM-002	Eagle Eye Camera Pole Mount
EN-CACM-002	Eagle Eye Camera Corner Mount